

Phone: 818-485-0500 FAX: 818-485-0540

Outside CA: 1-800-RRRIVET www.hansonrivet.com






Capacity: up to 1/4" diameter: Stainless standard open end blind rivets 9/32" diameter in Aluminum standard open end blind rivets.

POWERBIRD GOLD


Weight: 4.8 lbs. - Pulling Force: 3,960 lbs. Stroke: .790" Nose Pieces Included: 5/32" 3/16",1/4 "& 9/32"

Complete with carrying case battery & charger.





RIVET MATERIAL		STANDARD COMMERCIAL OPEN-END RIVETS					
BODY	MANDREL	3/32	1/8	5/32	3/16	1/4	9/32
ALUMINUM	ALUMINUM	•	•	•	•	•	•
ALUMINUM	STEEL	•	•	•	•	•	
STEEL	STEEL	•	•	•	•	•	
STAINLESS	STEEL	•	•	•	•	•	
STAINLESS	STAINLESS	•	•	•	•	•	



APPROXIMATE RIVETS PER CHARGE

RIVET BODY DIAMETER	MATERIAL	RIVETS/CHARGE	
3/32	ALUMINUM	1,900	
1/8	ALUMINUM	1,300	
1/8	STEEL	1,100	
1/8	STAINLESS	1,000	
5/32	ALUMINUM	1,000	
5/32	STEEL	900	
5/32	STAINLESS	800	
3/16	ALUMINUM	700	
3/16	STEEL	500	
3/16	STAINLESS	400	
1/4	ALUMINUM	300	
1/4	STEEL	180	
1/4	STAINLESS	100	
9/32	ALUMINUM	300	

SPECIAL LONG NOSEPIECES *

RIVET DIAMETER	PART NUMBER	" <mark>A</mark> " SHANK LENGTH	"B" SHANK DIA.
3/32"	RTP-7252121	.315	.236
1/8"	RTP-7252148	.315	.236
5/32"	RTP-7252156	.315	.314
3/16"	RTP-7252172	.315	.393
*Long nosepieces may require special long mandrels			
		_	

STANDARD NOSEPIECES

TYPE OF RIVET	RIVET DIAMETER	NOSEPIECE
	3/32	RTP-7252075
	1/8	RTP-7251583
OPEN-END	5/32	RTP-7252040
RIVET	3/16	RTP-7252067
	1/4	RTP-7252560
	9/32	RTP-7252237

REPLACEMENT JAWS			
	RTP-7102208		
	RTP-71515247 FOR 9/32" DIA.		

REPLACEMENT BATTERIES & CHARGERS

Battery Part Number	Battery Specification	Charger Part number	Charger Specification
RTP-7251045	14.4V 1.3AH Li-lon	RTP-7251138	14.4V Li-lon
RTP-7251049	14.4V 2.6AH Li-lon	RTP-7251138	14.4V Li-lon

Batteries

Due to European environmental regulations, we will no longer be supplying 12V Nickel-Cadmium (NI-Cd) batteries. Once exiting inventories are gone, they will not be available for sale or replacement. The 12V 3.2AH Nickel-Metal Hydride (Ni-MH) battery will still be available for sale. In addition to this change, a new product line of 14.4V Lithium Ion (Li-Ion) batteries will be available for sale. The new 14.4V Li-Ion batteries will be available in 2 sizes: 1.3AH and 2.6AH. All Li-Ion batteries will require 14.4V Li-Ion chargers.

<u>Chargers</u>

As a result of the change to the batteries, a new 14.4V Lithium Ion (Li-Ion) charger will be available for sale. Also, the Ni-Cd + Ni-MH charger will remain available for sale.

Battery Powered Tools

Once existing inventories of standard Accubirds, Powerbirds and Firebirds are gone, they will no longer come with Nickel-Cadmium batteries. All new inventories of standard Accubirds, Powerbirds Firebirds will come with 14.4V Li-Ion batteries and chargers. The Accubird and Firebird will come standard with the 14.4V 1.3AH Li-Ion battery. The 14.4V 2.6AH Li-Ion battery can be bought separately as an accessory for these 2 tools. The Powerbird will come standard with the 14.4V 2.6AH Li-Ion battery.

Compatibility

Due to the change in batteries and chargers, it is important to note that <u>certain batteries</u> <u>are only compatible with certain chargers</u>.

Ni-Cd batteries must only be charged with Ni-Cd + Ni-MH chargers. An exception to this to this is that some older style chargers are Ni-Cd only.

Ni-MH batteries must only be charged with Ni-Cd + Ni-MH chargers.

Li-lon batteries must only be charged with Li-lon chargers.

All chargers are labeled with the correct battery compatibility. Refer to the table above determine to the correct charger for the battery in use. When in doubt contact us directly at 1-800-777-4838 for technical assistance.